

MGA-1000

Zeeman Graphite Furnace Atomic Absorption Spectrometer



MGA-1000 is a graphite furnace atomic absorption spectrometer based on Zeeman High Frequency Polarization Modulation (ZHFP) technique. It is intended for determination of a wide range of elements in various types of samples (water, soil, foodstuffs, fodders, pharmaceuticals, etc.). The instrument provides high selectivity and sensitivity of the analysis.

FEAUTURES AND ADVANTAGES

- Simultaneous measurement of total and background absorptions
- Quasi-double beam optics eliminating drifts and enabling direct operation with no warm-up needed
- Compact and effective cooling system
- Smart 47-position autosampler
- Cold Vapor/Hydride generator available
- Stabilized temperature platform furnace (STPF) concept implemented
- Bright Electrodeless Discharge Lamps (EDL) providing low detection limits and direct As and Se determination at levels from 1 ppb without hydride generation technique
- Routine analysis of Na, K, Mg, and Ca
- «Eltherm» software compliant with 21 CFR part 11
- IQ/OQ protocols
- Noiseless operation

ANALYTES

1 H		Limits of detection (LOD) for model samples ■ < 0.1 ppb ■ 0.1–1 ppb ■ > 1 ppb																2 He
3 Li	4 Be											5 B	6 C	7 N	8 O	9 F	10 Ne	
11 Na	12 Mg											13 Al	14 Si	15 P	16 S	17 Cl	18 Ar	
19 K	20 Ca											21 Sc	22 Ti	23 V	24 Cr	25 Mn	26 Fe	27 Co
37 Rb	38 Sr	39 Y	40 Zr	41 Nb	42 Mo	43 Tc	44 Ru	45 Rh	46 Pd	47 Ag	48 Cd	49 In	50 Sn	51 Sb	52 Te	53 I	54 Xe	
55 Cs	56 Ba	57–71 La-Lu	72 Hf	73 Ta	74 W	75 Re	76 Os	77 Ir	78 Pt	79 Au	80 Hg	81 Tl	82 Pb	83 Bi	84 Po	85 At	86 Rn	

APPLICATIONS

- Environmental monitoring
- Water treatment
- Food and beverages
- Agriculture
- Pharmaceuticals and life science
- Medicine and biochemistry
- Forensics and clinical research
- Petrochemistry and refineries
- Process control and material analysis
- Science and research

The lists of standards (ISO, ASTM, EN, EPA, AOAC, etc.) applicable to MGA-1000 spectrometer are available at lumexinstruments.com

LOW COST ANALYSIS

- Standard graphite tubes (28 mm) of both Massman and L'vov types are available
- The standard centrifuge-type tubes are used with autosampler
- Prolonged tube lifetime
- Low argon consumption

SPECIFICATIONS

Wavelength range	185–900 nm
Maximal temperature of the furnace atomizer	3000 °C
Furnace heating rate	up to 4500 K/sec
Spectral lamps	Hollow Cathode Lamps Electrodeless Discharge Lamp
Argon flow rate (high purity argon)	< 2 l/min
Typical tube lifetime	up to 800 analysis cycles
Autosampler capacity	47 samples
Power supply	Three-phase 220/380VAC, 50/60 Hz or 120/208 VAC, 50/60 Hz
Power consumption	0.1 kW in standby 6 kW in atomization mode
Dimensions (L×W×H), weight	800 × 310 × 475 mm, 50 kg

WARRANTY

MGA-1000 AA spectrometer is covered by a full 1-year warranty.

SERVICE

Installation and commissioning of Lumex instruments' AA spectrometers can be carried out at a customer site by our service engineers or by certified distributor.



Find your local Lumex Instruments distributor:
www.lumexinstruments.com | sales@lumexinstruments.com